



Product Specification Report

ARMOR ALL PROFESSIONAL®

AHS CERAMIC SEAL

CLASSIFICATION

- Ceramic Protectant

PRODUCT DESCRIPTION

- White foaming liquid concentrated product that protects vehicle surfaces. AAP® Ceramic Seal's synthetic polymer based ceramic technology actively bonds to previously applied layers to deliver three times the shine and protection.

FEATURES & BENEFITS

- AAP® AHS Ceramic Seal's synthetic polymer based ceramic technology forms a durable and strong protective coating on the vehicle surface
- Actively bonds and seals in previously applied product chemistries to increase the longevity of the shine and protection
- Can be applied late in the tunnel/wash process, stimulates/enhances drying
- Tropical fruit scented
- White foaming application, low to medium foam level depending on applicator
- Reclaim compatible
- Achieve 3 times the shine and protection when layering Ceramic Seal over the proven formulas of Rain-X and Extreme Shine Wax to deliver a top package with next level performance.

PHYSICAL CHARACTERISTICS

- Form Liquid
- Color Amber
- Odor Tropical fruit
- Foam White
- pH (Conc.) 7.0
- Specific Gravity 0.95
- Pounds per gallon 7.9
- Kilograms per liter 0.95
- Hard water tolerant
- Fully biodegradable

PACKAGE SIZES & PRODUCT NUMBERS

Size Available	Product Number
4x1GAL (15.2 L)	V35724

Armor All Professional® AHS Ceramic Seal

APPLICATION GUIDE / USE INSTRUCTIONS

Recommended Product Dosing

- Apply between 0.5 – 0.75 oz. on average per car for optimal Ceramic protection

Application Dilution

- Ratio varies depending on applicator type

Application Equipment

- For best results, apply through Zep Vehicle Care's AAP® Ceramic Seal Arch with elbow foamers w/v-jet nozzels
- Alternatively, apply through standard elbow or K-stick foamers, or through a foaming rainbar.

DOSING MEASUREMENT

Please conduct a volumetric measurement

HEALTH, SAFETY, STORAGE & FIRST AID INFORMATION

See Product SDS: <https://zsds3.zepinc.com/>