

Cover Sheet for Safety Data Sheet

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Name AAP AHS EXTREME SHINE WAX CS 4X1GL

V30424

Overseas Supplier NCS Vehicle Care

NZ Distributor Velocity Vehicle Care NZ Ltd

Level 4

3 London St, Hamilton, 3240

Phone: 0800 464 249

Email: orders@velocityvehiclecare.com

Emergency Number New Zealand: 0800 243 622

This product is Hazardous according to the NZ Hazardous Substances (Classification) Regulations 2001.

Australian Distributor Velocity Vehicle Care Pty Ltd

10 Holmwood Rd Tottenham VIC 3012 Ph: 1300 990 074

Email: orders@velocityvehiclecare.com

Emergency Number Australia: 1800 127 406

This product is Hazardous according to the Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004]



AAP AHS EXTREME SHINE WAX CS 4X1GL

Version 4.5 Revision Date 05/20/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : AAP AHS EXTREME SHINE WAX_CS 4X1GL

Material number : V30424

Manufacturer or supplier's details

Company : NCS Vehicle Care, Inc.

Address : 1997 American Blvd.

De Pere, WI 54115

Telephone : 877-326-9274

Emergency telephone numbers

For SDS Information : www.ncsvehiclecare.com

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Protective Coating

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid	
Colour	purple	
Odour	like fruit	

GHS Classification

Skin irritation : Category 2 Serious eye damage : Category 1

GHS label elements

Hazard pictograms

TE

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with



AAP AHS EXTREME SHINE WAX CS 4X1GL

Version 4.5 Revision Date 05/20/2022

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
dodecyldimethylamine oxide	1643-20-5	>= 10 - < 20
2-butoxyethanol	111-76-2	>= 5 - < 10
1-Propanaminium, 3-amino-N-(carboxymethyl)-	61789-40-0	>= 3 - < 5
N,N-dimethyl-, N-coco acyl derivs., hydroxides,		
inner salts		
Quaternary ammonium compounds, dicoco	61789-77-3	>= 3 - < 5
alkyldimethyl, chlorides		
N,N-dimethyltetradecylamine N-oxide	3332-27-2	>= 3 - < 5
citric acid	77-92-9	>= 1 - < 3
(2-methoxymethylethoxy)propanol (Mixture of	34590-94-8	>= 1 - < 3
isomers)		

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

If in eyes, rinse with water for 15 minutes.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.



AAP AHS EXTREME SHINE WAX CS 4X1GL

Version 4.5 Revision Date 05/20/2022

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

Smoke

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.



Version 4.5 Revision Date 05/20/2022

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Observe label precautions.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
(2- methoxymethylethoxy)propano I (Mixture of isomers)	34590-94-8	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		ST	150 ppm 900 mg/m3	NIOSH REL
		TWA	100 ppm	NIOSH REL



AAP AHS EXTREME SHINE WAX CS 4X1GL

Version 4.5 Revision Date 05/20/2022

	600 mg/m3	
TWA	100 ppm	OSHA Z-1
	600 mg/m3	
TWA	100 ppm 600 mg/m3	OSHA P0
STEL	150 ppm 900 mg/m3	OSHA P0
STEL	150 ppm 900 mg/m3	CAL PEL
PEL	100 ppm 600 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As	200.mg/g Creatinine	ACGIH BEI
				soon as possible		
				after		
				exposure		
				ceases)		
2-BUTOXYETHANOL		Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI
		acid (BAA)		shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.



Version 4.5 Revision Date 05/20/2022

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : purple
Odour : like fruit

Odour Threshold : No data available

pH : 5 - 5.5, 1 %(as aqueous solution)

Melting point/freezing point : < -6.67 °C

Boiling point : No data available

Flash point : 93.3 °C

Method: closed cup

Evaporation rate : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.979 - 0.995 g/cm3

Solubility(ies)

Water solubility : No data available Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.



Version 4.5 Revision Date 05/20/2022

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke). Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 2,649 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 139.18 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg



AAP AHS EXTREME SHINE WAX CS 4X1GL

Version 4.5 Revision Date 05/20/2022

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

citric acid:

Acute oral toxicity : LD50 Oral Rat: 5,400 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: Causes skin burns.

Components:

N,N-dimethyltetradecylamine N-oxide:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Components:

N,N-dimethyltetradecylamine N-oxide:

Remarks: No data available

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information



Version 4.5 Revision Date 05/20/2022

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

N,N-dimethyltetradecylamine N-oxide:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and

other aquatic invertebrates

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: No data available

: Remarks: No data available

octanol/water Components:

(2-methoxymethylethoxy)propanol (Mixture of isomers):

Partition coefficient: n-: Pow: 0.0043

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

40 CFR Protection of Environment; Part 82 Protection of Regulation

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life.

The GHS H401 statement "Toxic to aquatic life" noted

above is an Acute Aquatic Toxicity Category 2

classification. Although the product has the potential to harm the environment, it is not classified as a marine pollutant or regulated under transportation regulations.



Version 4.5 Revision Date 05/20/2022

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.



AAP AHS EXTREME SHINE WAX CS 4X1GL

Version 4.5 Revision Date 05/20/2022

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ethyl acetate	141-78-6	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
formaldehyde	50-00-0	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Serious eye damage or eye irritation

Skin corrosion or irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-butoxyethanol 111-76-2 7.9036 %

California Prop. 65



WARNING: This product can expose you to chemicals including dichloroacetic acid, which is/are known to the State of California to cause cancer and birth defects or other

reproductive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL This product contains the following components listed on the Canadian

NDSL. All other components are on the Canadian DSL.

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)




Version 4.5 Revision Date 05/20/2022

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word Hazard statements Precautionary statements

Causes skin irritation. Causes serious eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/eye protection/face protection.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before

reuse.

Version:	4.5
Revision Date:	05/20/2022
Print Date:	05/19/2022

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.



AAP AHS EXTREME SHINE WAX_CS 4X1GL

Version 4.5

Revision Date 05/20/2022

