

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : SOILAWAY
Product code : 7600100

1.2. Other means of identification

Other means of identification : Vehicle Wash

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Industrial Cleaning Agent
Restrictions on use : For Industrial Use Only

1.4. Details of manufacturer or importer

Supplier
VELOCITY VEHICLE CARE
5 Horsburgh Drive
Altona North Victoria 3025
Australia
T 1300 990 074
<https://www.velocityvehiclecare.com/>

1.5. Emergency phone number

Emergency number : Australia 1800 127 406 New Zealand 0800 483 562

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Skin corrosion/irritation, Category 1 H314
Serious eye damage/eye irritation, Category 1 H318

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Corrosion

Signal word (GHS AU) :

Danger

Contains :

Sodium Metasilicate (1 – 10 %); Ethylene Diamine Tetraacetic Acid- Tetrasodium salt (1 – 10 %); Alpha Olefin Sulphonate (10 – 30 %)

Hazard statements (GHS AU) :

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS AU) :

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear face shield, protective clothing, protective gloves.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional hazard statements (GHS AU) : For exposure advice within Australia contact the Poisons Information Centre 131 126.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Alpha Olefin Sulphonate	68439-57-6	10 – 30	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401
Sodium Metasilicate	10213-79-3	1 – 10	Met. Corr. 1, H290 Skin Corr. 1B, H314 STOT SE 3, H335
Ethylene Diamine Tetraacetic Acid- Tetrasodium salt	64-02-8	1 – 10	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Ethylene Glycol Butyl Ether	111-76-2	1 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315
Other substances (not contributing to the classification of this product)	-	To 100%	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code : 2X

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store locked up.

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethylene Glycol Butyl Ether (111-76-2)

Australia - Occupational Exposure Limits

Local name	2-Butoxyethanol
OES TWA	96.9 mg/m ³
	20 ppm
OES STEL	242 mg/m ³
	50 ppm

8.2. Monitoring methods

Monitoring methods : Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Safety shower with an appropriate liquid. Ocular shower with suitable liquid.

Hand protection : Wear gloves resistant to chemical penetration: Polyvinylchloride (PVC), Nitrile rubber (NBR), Butyl rubber (IIR)

Eye protection : Wear eye protection: Chemical goggles or safety glasses

Skin and body protection : Wear foot protection: Chemical resistant boots. Wear protective clothing: Impervious clothing. Use protective apron: Chemical resistant apron

Respiratory protection : Use a half mask to protect the face from liquid splashes

Personal protective equipment symbol(s)



Other information : The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210. PPE compliant with the recommended standards should be selected.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance : No data available

Colour : light yellow

Odour : characteristic

Odour threshold : No data available

pH : No data available

pH solution : 10.5 – 12.0 1%v/v

Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : < 0 °C

Boiling point : ≈ 100 °C

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: 1.07 – 1.11
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
Fat solubility	: No data available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Sodium Metasilicate (10213-79-3)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: Before neutralisation, the product may represent a danger to aquatic organisms.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

SOILAWAY

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Sodium Metasilicate (10213-79-3)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Ethylene Glycol Butyl Ether (111-76-2)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Ethylene Diamine Tetraacetic Acid- Tetrasodium salt (64-02-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Alpha Olefin Sulphonate (68439-57-6)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SOILAWAY

Fluorinated greenhouse gases	False
------------------------------	-------

Sodium Metasilicate (10213-79-3)

Fluorinated greenhouse gases	False
------------------------------	-------

Ethylene Glycol Butyl Ether (111-76-2)

Fluorinated greenhouse gases	False
------------------------------	-------

Ethylene Diamine Tetraacetic Acid- Tetrasodium salt (64-02-8)

Fluorinated greenhouse gases	False
------------------------------	-------

Alpha Olefin Sulphonate (68439-57-6)

Fluorinated greenhouse gases	False
------------------------------	-------

SECTION 13: Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
3266	3266	3266
14.2. UN Proper Shipping Name		
CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium Metasilicate)	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium Metasilicate)	Corrosive liquid, basic, inorganic, n.o.s. (Sodium Metasilicate)

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

ADG	IMDG	IATA
14.3. Transport hazard class(es)		
8	8	8
		
14.4. Packing group		
III - Substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 3266
Special provision (ADG) : 223, 274
Limited quantities (ADG) : 5I
Excepted quantities (ADG) : E1
Packing instructions (ADG) : P001, IBC03, LP01
Portable tank and bulk container instructions (ADG) : T7
Portable tank and bulk container special provisions (ADG) : TP1, TP28

Transport by sea

UN-No. (IMDG) : 3266
Special provisions (IMDG) : 223, 274
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP28
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG) : A
Stowage and handling (IMDG) : SW2
Segregation (IMDG) : SGG18, SG35
Properties and observations (IMDG) : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

Air transport

UN-No. (IATA) : 3266
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 852
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 856
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A803
ERG code (IATA) : 8L

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

14.8. Hazchem or Emergency Action Code

Hazchem Code : 2X

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Contains substance(s) listed on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Caution

Australian Pesticides and Veterinary Medicines Authority (APVMA)

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Mandatory 5 year SDS review.

Data sources : Safe Work Australia- Code of Practice- Preparation of Safety Data Sheets for Hazardous Chemicals
Safe Work Australia- Code of Practice- Labelling of Workplace Hazardous Chemicals
NICNAS- Australian Inventory of Chemical Substances (AICS)
NICNAS- Relevant Chemical Assessment Reports
Safe Work Australia- Workplace Exposure Standards for Airborne Contaminants
United Nations- Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
Safe Work Australia- Hazardous Substances Information System (HSIS)
The National Transport Commission- Australian Dangerous Goods Code (ADG Code)
Relevant Raw Material Suppliers- Component Safety Data Sheets. Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals
Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals
Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants
Safe Work Australia - Hazardous Chemical Information System (HCIS)
Australian Inventory of Industrial Chemicals (AICIS Inventory)
Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020
Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017
Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017
New Zealand - Chemical Classification and Information Database (CCID)
New Zealand - Inventory of Chemicals (NZIoC)
European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)
European Chemicals Agency (ECHA) - REACH Study Results
European Chemicals Agency (ECHA) - REACH Registration Dossiers
United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
Uniform Scheduling of Medicines and Poisons (SUSMP)
United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)
Australian Dangerous Goods Code (ADG Code)
International Air Transport Association Dangerous Goods Regulations (IATA DGR)
International Maritime Dangerous Goods (IMDG Code).

Date of revision : 11/09/2026

SOILAWAY

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Other information

: EMERGENCY CONTACT NUMBER (Exposure and Environment): 1800 127 406. The information herein is to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions of application are beyond our control Velocity Vehicle Care Pty Ltd and its associated companies do not accept liability for any damages resulting from the use of, or reliance on, this information in inappropriate contexts.

Classification	
Skin Corr. 1	H314
Eye Dam. 1	H318

Full text of H-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 2	Hazardous to the aquatic environment – Acute Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life

Safety Data Sheet (SDS), Australia

The information herein is to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions of application are beyond our control Velocity Vehicle Care Pty Ltd and its associated companies do not accept liability for any damages resulting from the use of, or reliance on, this information in inappropriate contexts.