

Product Specification Report



ARMOR ALL PROFESSIONAL®

CERAMIC SEAL

CLASSIFICATION

Ceramic Protectant •

PRODUCT DESCRIPTION

• White foaming liquid concentrated product that protects vehicle surfaces. AAP[®] Ceramic Seal's synthetic polymer based ceramic technology actively bonds to previously applied layers to deliver three times the shine and protection.

FEATURES & BENEFITS

- AAP[®] Ceramic Seal's synthetic polymer based ceramic technology forms a durable and strong • protective coating on the vehicle surface
- Actively bonds and seals in previously applied product chemistries to increase the longevity of the shine and protection
- Can be applied late in the tunnel/wash process, stimulates/enhances drying
- Tropical fruit scented
- White foaming application, low to medium foam level depending on the applicator •
- Reclaim compatible •
- Use AAP® Ceramic Seal to seal the unparalleled protection of Rain-X® Complete Surface Protectant and • premier AAP[®] Extreme Shine Wax

PHYSICAL CHARACTERISTICS

- Form Liquid • Light amber Color
- Odor **Tropical fruit**
- Foam White
- pH (Conc.)
- 7.3 Specific Gravity 0.97
- Pounds per gallon 8.1
- Kilograms per liter 0.97
- Hard water tolerant
- Fully biodegradable

PACKAGE SIZES & PRODUCT NUMBERS

Size Available	Product Number
2x2.5 GAL (18.9 L)	V35836

APPLICATION GUIDE / USE INSTRUCTIONS

Recommended Product Dosing

• Apply between 1 – 1.5 oz. on average per car for optimal Ceramic protection

Application Dilution

• Ratio varies depending on applicator type

Application Equipment

- For best results, apply through NCS Vehicle Care's AAP[®] Ceramic Seal Arch with elbow foamers w/vjet nozzels
- Alternatively, apply through standard elbow or K-stick foamers, or through a foaming rainbar.

DOSING MEASUREMENT

Please conduct a volumetric measurement

HEALTH, SAFETY, STORAGE & FIRST AID INFORMATION

See Product SDS: sds.zepinc.com

